# PLU ALU STONE WOOL BOARDS





Code certification CE: MW - EN 13162 - T3- MU1



# **TECHNICAL SPECIFICATION**

Boards made from ISOVER stone wool and faced with Aluminium foil. The boards are obtained by melting the mineral raw materials in a furnace, fiberising the melt by REX process, spraying a a binder and adding mineral oils for

protection against dust and water repellence. The mineral fibers mat is faced with Aluminium foil and processed into boards, which are packaged on the production line.

# **APPLICATION**

ISOVER PLU ALU boards are used for thermal, acoustic and fire insulation in civil and industrial buildings:

- metallic buildings walls
- wooden houses walls

# PACKAGING, TRANSPORT, WAREHOUSING

ISOVER PLU ALU boards are packaged in PE foil. The boards must be transported and stored avoiding contact with water, or other damage.

# **BENEFITS**

- high thermal insulation performance (low thermal conductivity)
- fire safety non combustible material
- excellent acoustic properties (high absorption coefficient)
- easy to handle, non-toxic
- low vapour flow resistance
- long term resistance in vertical position
- environment friendly and hygienic
- completely hydrophobic is made water repellent
- long life span and time-stable properties
- resistant to mould, mildew, rodents and insects
- chemically neutral, non-corrosive
- easy workability can be cut, drilled etc.

# **CERTIFICATES, STANDARDS, APPROVALS**

- EC Certificate: 1840-DPC-99/91/EC/0114-07
- ISO 9001, ISO 14001, OHSAS 18001

# **TECHNICAL PARAMETERS**

PARAMETER	UNIT	VALUE				
THERMAL INSULATION PROPERTIES						
Declared thermal conductivity $\lambda_D$	W/(m K)	0,037				
FIRE SAFETY PROPERTIES						
Reaction to fire	-	A2-s1, d0				
OTHER PROPERTIES						
Maximum temperature for use	°C	200				
Melting temperature	°C	≥ 1000				

#### **DIMENSIONS AND PACKAGING**

Product	Thickness (mm)	Length * Width (mm)	Dimension per package (m²/package)	Declared thermal resistance R <sub>D</sub> (m <sup>2</sup> .K/W)
PLU 40 ALU	40	1000 x 600	4,80	1,05
PLU 50 ALU	50	1000 x 600	4,80	1,35
PLU 60 ALU	60	1000 x 600	3,60	1,60
PLU 80 ALU	80	1000 x 600	2,40	2,15
PLU 100 ALU	100	1000 x 600	2,40	2,70
PLU 120 ALU	120	1000 x 600	2,40	3,20



20.10.2012. Declared characteristics are valid at the date of publishing. The manufacturer reserves the right to change them.

