

Designation code CE: MW-EN13162-T4-AFr10-WS-WL(P)-MU1

# ISOVER EASY VENT NT



STONE WOOL BOARDS

## Benefits

### HIGH QUALITY

-  **High thermal insulation performance** (low thermal conductivity);
-  **Fire safety** (noncombustible material);
-  **Excellent acoustic properties** (high absorption coefficient);
-  **Long life span and time-stable properties;**
-  **Low vapor flow resistance;**
-  **Resistant to mold, mildew, rodents and insects;**

### ECONOMIC VALUE

-  **Contributes to the reduction of energy consumption;**
-  **Chemically neutral, non-corrosive, easy to handle, non-toxic;**

## TECHNICAL SPECIFICATION

Boards made from ISOVER stone wool coated with black nonwoven fiberglass fabric. The boards are obtained by melting the mineral raw materials in a furnace, fiberizing the melt by REX process, spraying a binder and adding mineral oils for protection against dust and water repellence. The mineral fibers mat is processed into boards which are packaged on the production line.

## APPLICATION

Use (according to standard EN 13162:2012 + A1:2015): Thermal insulation for buildings (ThiB).

ISOVER EASY VENT NT boards are used for thermal, acoustic and fire insulation in civil and industrial buildings:

- ventilated facades;
- curtain walls;
- ceilings (cellars and underground garages);
- wooden houses walls or metallic buildings walls;
- walls made of metal boxes for halls;

## PACKAGING

ISOVER EASY VENT NT boards are packed in packages wrapped in PE foil, and the packages are packed in pallets.





# ISOVER

## EASY VENT NT

STONE WOOL BOARDS

Designation code CE: MW-EN13162-T4-AFr10-WS-WL(P)-MU1

TECHNICAL PARAMETERS	U.M.	VALUE
<b>THERMAL INSULATION PROPERTIES</b>		
Declared thermal conductivity - $\lambda_D$	W/(m•K)	0.036
<b>FIRE SAFETY PROPERTIES</b>		
Reaction to fire	-	A1
Melting temperature (according DIN 4102-17)	°C	≥ 1000
<b>OTHER PROPERTIES</b>		
Air flow resistivity AFr	kPa•s/m <sup>2</sup>	≥ 10
Specific heat capacity $c_p$ (according EN ISO 10456)	J/(kg•K)	1030
Short term water absorption $W_p$ / Long term water absorption $W_{lp}$	kg/m <sup>2</sup>	max. 1 / max. 3
Water vapour diffusion resistance factor $\mu$ , MU	-	1
Thickness tolerances	Class	T4
Chemical behavior	Chemically neutral. Does not retain moisture. Allows vapors diffusion.	



# ISOVER

## EASY VENT NT

STONE WOOL BOARDS

Designation code CE: MW-EN13162-T4-AFr10-WS-WL(P)-MU1

### DIMENSIONS AND PACKAGING

PRODUCT	Thickness (mm)	Length x Width (mm)	Area (m <sup>2</sup> /package)	Number of packs/pallet	Area (m <sup>2</sup> /pallet)	Declared thermal resistance R <sub>D</sub> (m <sup>2</sup> ·K/W)
EASY VENT NT	80	1000 x 600	4.2	8	33.6	2.20
EASY VENT NT	100	1000 x 600	3.6	8	28.8	2.75
EASY VENT NT	120	1000 x 600	3.0	8	24.0	3.30
EASY VENT NT	140	1000 x 600	2.4	8	19.2	3.85
EASY VENT NT	150	1000 x 600	2.4	8	19.2	4.15
EASY VENT NT	160	1000 x 600	1.8	10	18.0	4.40
EASY VENT NT	180	1000 x 600	1.8	8	14.4	5.00
EASY VENT NT	200	1000 x 600	1.8	8	14.4	5.55
EASY VENT NT	220	1000 x 600	1.2	10	12.0	6.10
EASY VENT NT	240	1000 x 600	1.2	10	12.0	6.65
EASY VENT NT	250	1000 x 600	1.2	8	9.6	6.90

### RECOMMENDATION

During installation: mineral wool boards must be dry, clean, without traces of dust or other impurities. Moisture and water damages the properties of mineral wool. The thermal insulation must be protected against the action of moisture, whether it is generated by condensation, by an accident during installation or caused by flooding due to faulty installation.

### CERTIFICATES, STANDARDS, APPROVALS

- Certificate of constancy of performance:  
1840-CPR-99/91/EC/0868-24
- Certificate of Management System:  
ISO 9001:2015  
ISO 14001:2015  
ISO 45001:2018

### TRANSPORT AND STORAGE

The boards must be transported, stored and installed avoiding contact with water, or other damage. Packages or boards will not be stored in direct contact with the ground.

### INSTALLATION

During installation, ensure that the insulation is continuous, without gaps or free spaces, without leaks at the joints between the boards or in the end or perimeter areas. Installation of the mineral wool boards will be done according to the manufacturer's instructions or the cladding system supplier's instructions in accordance with the designer's recommendations. For walls with a ventilated facade or walls made of metal boxes, the boards are installed with the facing the outside of the insulated enclosure. In this way, the fiberglass facing will protect against the penetration of humidity and the circulation of air currents.

### SAFETY INSTRUCTIONS

Before start using the product, consult the technical safety data sheet and the information printed on the packaging. As personal protection, the use of protective gloves is recommended.

*ISOVER is a registered trademark of Saint-Gobain. The information contained herein reflects the latest data based on our current knowledge and experience and are subject to change without prior notice as a result of technical or production changes. Please ensure you always have the latest version of this document by accessing our site at the following address: [www.isover.ro](http://www.isover.ro). This document contains only general recommendations and does not address special circumstances.*

*Prior to installation, please ensure that you have thoroughly read and understood the specifications of your project, that you have tested the product for your specific purpose, and that the selected product will enable the required outcome. The information presented in this document does not constitute a guarantee as to certain properties of the product or compatibility for a specific use, hence Saint-Gobain Group cannot be held responsible for the quality of the installation works.*